




AZARIOTM

INTERNATIONAL


















SPC FLOORING


Waterproof Rigid Core Vinyl Tiles




NEW COLLECTION JUNE - 2023

Why SPC Flooring?

-  Lower Thickness & Weight
-  Impact Resistances
-  Easy to Clean Floor
-  Stain Free
-  Green Product
-  Dust free Installaion
-  Flame Resistant
-  Scratch Resistant
-  Easy to Carry
-  Modular
-  Glue Free
-  Less Dead Weight
-  Quick Installaion
-  Recyclable
-  Weather Proof
-  Termite Resistant
-  Water Proof




CLICK TILE



Easy & Hassle Free Installation

Structure



UV Coating

Reduce fading to sun light near window or any other indoor environment

Wear Layer

Strong wear-resistance for foot trac and make the surface scratch resistance.

Decor Film

A design layer of high-resolution photo of real wood that is reproduced with sophisticated printing techniques.

SPC Core Sheet

primary layer of the SPC structure

Underlayment

Effective sound reduction and cushioning incorporates amoisture barrier and mold repellent



Ala
mo



181x1220x5mm






Design :
ALAMO

Size :
181x1220mm

Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Ath
ena



181x1220x5mm






Design :
ATHENA

Size :
181x1220mm


Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Ba
Ri



181x1220x5mm






Design :
BARI

Size :
181x1220mm


Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Bit
Ola



181x1220x5mm






Design :
BITOLA

Size :
181x1220mm

Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Cl
ir a



181x1220x5mm







Design :
CLAIR

Size :
181x1220mm

Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Expre
SSO



181x1220x5mm






Design :
EXPRESSO

Size :
181x1220mm

Thickness :
5mm



CLICK TILE




Easy & Hassle Free Installation





Flu
id



181x1220x5mm






Design :
FLUID

Size :
181x1220mm

Thickness :
5mm



CLICK TILE




Easy & Hassle Free Installation





Kodi
ak



181x1220x5mm






Design :
KODIAK

Size :
181x1220mm


Thickness :
5mm



CLICK TILE




Easy & Hassle Free Installation





L
u
na



181x1220x5mm







Design :
LUNA
Size :
181x1220mm
Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Milano



181x1220x5mm






Design :
MILANO

Size :
181x1220mm

Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Ne
on



181x1220x5mm






Design :
NEON

Size :
181x1220mm

Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Op
al



181x1220x5mm






Design :
OPAL

Size :
181x1220mm


Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Op
tra



181x1220x5mm






Design :
OPTRA

Size :
181x1220mm


Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Ori
an



181x1220x5mm






Design :
ORIAN

Size :
181x1220mm

Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Qua
nta



181x1220x5mm






Design :
QUANTA

Size :
181x1220mm

Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





sed
ona



181x1220x5mm







Design :
SEDONA

Size :
181x1220mm


Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





S of
ia



181x1220x5mm






Design :
SOFIA

Size :
181x1220mm


Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Tre
nz



181x1220x5mm







Design :
TRENZ

Size :
181x1220mm

Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





Twilight



181x1220x5mm






Design :
TWILIGHT

Size :
181x1220mm


Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





veli
sh



181x1220x5mm







Design :
VELISH

Size :
181x1220mm

Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





vero
na



181x1220x5mm






Design :
VERONA

Size :
181x1220mm

Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





zi
on



181x1220x5mm







Design :
ZION
Size :
181x1220mm
Thickness :
5mm



CLICK TILE



Easy & Hassle Free Installation





SPC Flooring Technical Data

CHARACTERISTICS	STANDARDS			
	EN	Result	ASTM	Result
Size	EN 427	Pass	ASTM F536	Pass
Overall Thickness	EN 428	Pass	ASTM F36	Pass
Wear Layer Thickness	EN 429	Pass	ASTM F410	Pass
Dimension Squareness and Straightness	EN 427	Pass Squareness:0.18mm Straightness:0.07mm		
Chemical Resistance	EN 423	Pass	ASTM F925, ASTM F1344	Pass
Colour Fastness to Artificial Light	EN20105:B02 Method A	Pass, ≥ Grade 6	ASTM F1515	Pass
Heat Stability by Color Change			ASTM F1514	Pass
Castor Chair Suitability	EN 425	Pass		
Residual Indentation	EN 433	Pass,0.06mm	ASTM F1914, ASTM F970	Pass
Abrasion Group	EN 660-1/2	Group T	ASTM F510, ASTM D3384	Pass
Impact Resistance			ASTM F1265, ASTM D2632	Pass
Dimensional Stability	EN 434	Pass	ASTM F2199	Pass, 0.1%
Sound Reduction	ENISO717-2(ΔLw)	2 dB		
Flexibility	EN 435 Method A	Pass	ASTM F137	Pass
Slip Resistance	EN 13893	Class DS	ASTMD2047-93	Pass
Electrical Resistance	EN 1081 Method C	Pass	ASTM F150-06	Pass
Thermal Resistance	EN 12664	Pass		
Toxic Element Test	EN 71-3	Pass. Not toxic. Does not contain heavy metal and formaldehyde		
Behaviour to Fire	ENISO11925-2 EN13501-1 EN ISO 9239-1	Bf1-S1	ASTM E648-06	Pass/Class1
Smoke Density			ASTM E662	Pass,<450

Product Size & Packing Details

Size	1220 x 181 mm
SPC Core Thickness	4.00 mm to 6.00 mm
Wearlayer	0.30 mm (12mil) & 0.50 mm (20mil)
IXPE Underlayment	1 mm & 2 mm



AZARIOTM

INTERNATIONAL